

**Hochfester Klaviersaitenfederstahldraht  
„Röslau-Extra-Extra“**

**Music Spring Steel Wire  
„Röslau-Extra-Extra“**



mm Ø	Tol. mm	N/mm <sup>2</sup>	mm Ø	Tol. mm	N/mm <sup>2</sup>		
0,07	+/- 0,004	2790-3090	1,25	+/- 0,015	2450-2650		
0,08			1,30				
0,09			1,40				
0,10			+/- 0,008	2750-3040	1,50	+/- 0,020	2350-2500
0,11					1,60		
0,12					1,70		2300-2450
0,14					1,80		
0,16					1,90		2210-2350
0,18					2,00		
0,20					2,10		2110-2260
0,22	2,25						
0,25	2,40	2060-2210					
0,28	+/- 0,010	2750-2940			2,50		+/- 0,025
0,30			2,60				
0,32			2,80				
0,34			3,00	2010-2160			
0,36			3,20				
0,38			3,40				
0,40			3,60				
0,43			3,80	1860-2010			
0,45			4,00				
0,48			4,25	1770-1910			
0,50	+/- 0,015	2650-2840	4,50				
0,53			4,75				
0,56			5,00				
0,60			2600-2790				
0,63							
0,65							
0,70							
0,75							
0,80							
0,85							
0,90							
0,95							
1,00	2550-2750						
1,05							
1,10							
1,20			2450-2650				

**Stahl - und Drahtwerk Röslau GmbH  
Hofer Str. 16/17 D - 95195 Röslau**

**Tel.: (+49) 09238 / 80928 Fax: (+49) 09238 / 80910 eMail: g-gleissner@roeslau-draht.com**